| $\sim$ |   |   | 8 | w |     | M | - |   |
|--------|---|---|---|---|-----|---|---|---|
| S      | I | - | П | П | 0 8 |   | T | 3 |

|                                 | HX140B                    |  |
|---------------------------------|---------------------------|--|
|                                 |                           |  |
| Max. working height             | 15.9 m                    |  |
| Max. platform height            | 13.9 m                    |  |
| Max. horizontal outreach        | 13.2 m                    |  |
| Max. load capacity              | 250 kg                    |  |
| Platform inner size (I x w x h) | 1.8 x 0.75 x 1.1 m        |  |
| Platform rotator                | 180 degrees               |  |
| Travelling speed (low/high)     | 0.9/1.7 km/h              |  |
| Slewing angle                   | 360 degrees continuous    |  |
| Operating weight                | 7 850 kg                  |  |
| Transport length                | 6 200 mm                  |  |
| Transport width                 | 2 300 mm                  |  |
| Transport height                | 2 430 mm                  |  |
| Crawler shoe width              | 400 mm non-marking rubber |  |
| Engine                          | Kubota D1105-KB           |  |
| Max. output                     | 13.6 kW/2 200 rpm         |  |
| Fuel tank capacity              | 66 ltr                    |  |

## **Dimensions**

